



## LEAK DETECTION – UNIVERSAL DETECTORS


ESH offer a range of universal detectors that can work in direct conjunction with any control unit that can provide a 24V power supply and have the facility to receive a volt free signal in an alarm condition.

These units do not require Aqualarm control panels to monitor them.

### Detectors



**UDP-24**  
Point of use Detector.



**UDOF-24**  
Overflow Detector.



**UDC-24**  
Zone Module.




**UDR-24**  
Refrigerant Leak Detector.



**UDIN-24**  
Point of use Infra Red Detector.



**UDT-24**  
2 Stage Temperature Detector.



**UDF-24**  
Float Detector.



**UDH-24**  
Humidity Detector.

### CD-x Water Detecting Cables



Detecting Cable complete with male/female connections.

<b>CD-1</b>	1 metre	Code: 6004
<b>CD-2</b>	2 metre	Code: 6005
<b>CD-5</b>	5 metre	Code: 6006
<b>CD-10</b>	10 metre	Code: 6007

The model numbers for the Universal Version of each detectors are as follows:

Detector Description	Model Number
Point of use water detector	UDP-24
Cable zone detector module	UDC-24
Detection cable	CD-x
Infra-Red detector (oil or diesel)	UDIN-24
Float detector	UDF-24
Overflow detector	UDOF-24
Refrigerant gas detector	UDR-24
Temperature detector	UDT-24
Humidity detector	UDH-24

